

Mitsubishi Electric MSZ-LN



Produktinformation

| INOMHUDEL / UTOMHUDEL | | MSZ-LN25VG / MUZ-LN25VGHZ | MSZ-LN35VG / MUZ-LN35VGHZ | MSZ-LN50VG / MUZ-LN50VGHZ |
|---|---------------------|---------------------------------|---------------------------------|----------------------------------|
| Lägsta garanterade drifttemp. (Värme / Kyla) | °C | -35 / -10 | -35 / -10 | -35 / -10 |
| VÄRME | | | | |
| Energiklass värme klimat/kalt klimat | | A+++ / A+ | A+++ / A+ | A++ / A+ |
| SCOP / SCOP (kalt klimat) | | 5,2 / 4,0 | 5,1 / 4,0 | 4,6 / 3,4 |
| Dimensionerande effekt | kW | 3,2 | 4,0 | 6,0 |
| Värmeeffekt (Nominell) | kW | 3,2 | 4,0 | 6,0 |
| Effekt vid -15°C kW | kW | 3,2 | 4,0 | 6,0 |
| Värmeeffekt (Min-Max) | kW | 1,0 - 6,3 | 1,0 - 6,6 | 1,8 - 8,7 |
| KYLA | | | | |
| Energiklass | | A+++ | A+++ | A++ |
| SEER | | 10,5 | 9,4 | 7,6 |
| Dimensionerande effekt | kW | 2,5 | 3,5 | 5,0 |
| Kyleffekt (Nominell) | kW | 2,5 | 3,5 | 5,0 |
| Kyleffekt (Min-Max) | kW | 0,8 - 3,5 | 0,8 - 4,0 | 1,4 - 5,8 |
| INOMHUDEL | | | | |
| Dimensioner (B x H (I-See sensor) x D) | mm | 890 x 307(+34) x 233 | 890 x 307(+34) x 233 | 890 x 307(+34) x 233 |
| Vikt | kg | 35 | 36 | 55 |
| Luftflöde (Låg - Hög) | m ³ /min | 4.0 - 5.7 - 7.1 - 8.5 - 14.4 | 4.3 - 5.7 - 7.1 - 8.5 - 13.7 | 5.4 - 6.4 - 8.5 - 10.7 - 15.7 |
| Ljudnivå (SPL) (Låg - Hög) | dB(A) | 19 - 24 - 29 - 36 - 45 | 19 - 24 - 29 - 36 - 45 | 25 - 29 - 34 - 39 - 47 |
| Ljudnivå (PWL) | dB(A) | 58 | 58 | 60 |
| UTOMHUDEL | | | | |
| Dimensioner (B x H x D) | mm | 800 x 550 x 285 | 800 x 550 x 285 | 800 x 550 x 285 |
| Vikt | kg | 35 | 36 | 55 |
| Ljudnivå - Värme (SPL) | dB(A) | 49 | 50 | 54 |
| Ljudnivå - Kyla (SPL) | dB(A) | 46 | 49 | 51 |
| Rek. säkring | A | 10 | 13 | 16 |